


VILLA BARRIER SUN SHADE


سواتر جدارية للفلل



- 6-inch pipe thickness of 4 mm.
- 2.5 inch pipe thickness 3 mm.
- 2 inch pipe thickness 3 mm.
- Plate joints to assemble the canopy 12 mm.
- Canvas PVC German ten-year guarantee.
- Fabric (N.E.T.) German-made ten-year guarantee.
- Aluminum for installation cloth 4 cm 1.5 cm.
- Screws 16 mm solid steel with plastic cover for protection.
- Thermal dye is resistant to all weather conditions.
- Cement steel for the foundations of the canopy 85 x85 x85 cm.

- مقاطع بايب (٦) انش سماكة ٤ مم.
- مقاطع بايب (٢,٥) انش سماكة ٣ مم.
- مقاطع بايب (٢) انش سماكة ٣ مم.
- بليت لتجميع مفاصل المظلة ١٢ مم.
- قماش (بي في سي) الماني ضمان عشر سنوات.
- قماش (N.E.T.) الماني الصنع ضمان عشر سنوات.
- المنيوم للتثبيت القماش ٤ سم ١,٥ سم.
- براغي ستيل صلب ١٦ مم مع غطاء بلاستيك للحماية.
- صبغ حراري مقاوم لجميع الحالات الجوية.
- أسمنت صلب للأساسات المظلة ٨٥x ٨٥x ٨٥ سم.


Materials



- Tensile strength : 2200/200 N/5cm
- Tear Strength : 280/280 N
- Low Temperature-No Crack At : -30 C
- A : UV resistant .
- B : FR Flame Retardant .
- C : Warranty : 10 years .



- At Leeds we have large stocks of aluminium profiles and extrusions for all forms of tents and shading structures.



- Material : UV stablished HDPE
- Temperature range : -30 C to +75 C
- Tensile Strength - Weft : 635 N/50mm
- Tensile Strength - Weft : 2494 N/50mm
- Bursting Pressure (Mean) (AS 2001.2.4) : 3500 kPa
- UV Block : Up to 98.8%
- Warranty : 10 year UV*



Kedar

As part of our on-going service to the Marquee and Tent industry. We supply Brithish manufactured tent Kedar. Used to engance and stabilize tents and shades structures
The Kedar comes in two sizes. (8mm and 14mm)
* UK Manufactured



WHAT IS HOT DIP GALVANIZING ?

Hot Dip Galvanizing is a form of corrosion protection method, which involves coating an iron or steel structure with molten zinc.



SCREWS

Stocked in steel | zinc plating.
• Available in 18-8 stainless steel
• Hot dipped galvanized, plain, and black oxide.



GAS EPOXY MIO JOTUN

Paint epoxy high-quality composed of two compounds formed with a thickness large, anti-corrosive, contains chips iron oxide colored layer of a solid buffer against the passage of moisture and air pollutants and reflect UV rays and prevents access to the layer resin.



ALBASSAM S-050

VILLA BARRIER

SUN SHADE

سواتر جذابة للفناء





ALBASSAM S-022

VILLA BARRIER SUN SHADE

سواتر جدارية للفلل

